Supplement

Title: 9062 Users Supplement Issue: 1

Part Number: 2438554 Issue Date: 6/13 Print Date: April 2005 Page Count: 3

Revision/Date:

This supplement contains information necessary to ensure the accuracy of the above Instruction Sheet.



Change #1, 65801

On page 4, add the following **Warnings**:

- Use the Product only as specified, or the protection supplied by the Product can be compromised.
- Do not use the Product around explosive gas, vapor, or in damp or wet environments.

On page 5, replace the Recycling Information and the CAT III and add the following to the **Symbols** table:

<u>X</u>	This product complies with the WEEE Directive (2002/96/EC) marking requirements. The affixed label indicates that you must not discard this electrical/electronic product in domestic household waste. Product Category: With reference to the equipment types in the WEEE Directive Annex I, this product is classed as category 9 "Monitoring and Control Instrumentation" product. Do not dispose of this product as unsorted municipal waste. Go to Fluke's website for recycling information.
CAT II	Measurement Category II is applicable to test and measuring circuits connected directly to utilization points (socket outlets and similar points) of the low voltage mains installation.

6/13

CAT III	Measurement Category III is applicable to test and measuring circuits connected to the distribution part of the building's low-voltage MAINS installation.
	Conforms to relevant South Korean EMC Standards.
© ® Us	Conforms to relevant North American Safety Standards

On page 17, remove Pollution Degree 2, Type of Protection, Safety Specifications, Electrical Safety, Maximum Operating Voltage and Protection Level sections and add:

Safety.....IEC 61010-1: 300 V CAT III, Pollution Degree 2 IP Rating.....IEC 60529: IP40
Electromagnetic EnvironmentIEC 61326-1: Industrial

Electromagnetic Compatibility....... Applies to use in Korea only. Class A

Equipment (Industrial Broadcasting &

Communication Equipment) [1]

9062 Users

[1] This product meets requirements for industrial (Class A) electromagnetic wave equipment and the seller or user should take notice of it. This equipment is intended for use in business environments and is not to be used in homes.

Maximum Operating Voltage (U_{me}) 300 V AC for all ranges

On page 18, replace the following sections **Nominal Voltage Rotary Direction**, **Nominal Voltage Phase Indication** and **Nominal Test Voltage** with:

Nominal Voltage Rotary Direction 1 to 300 V ac

Nominal Voltage Phase Indication 120 to 300 V ac

Nominal Test Voltage (U_{me}) 1 to 300 V ac