

## CUSTO®Panel - D0 integrated fuse base

version with touch-safe protection, dual-function terminal on both sides



### D0 fuse base, version for distribution boards

Type	Rated voltage	Poles	Connection mm <sup>2</sup>	Pack size	Weight kg/100 u.	PG		Part No.
E 14 / 16 A / 1P	400 V	1-pole	1.5 - 35	9	7.6	03		<b>31301</b>
E 14 / 16 A / 3P		3-pole		3	23.0	03		<b>31302</b>
E 18 / 63 A / 1P		1-pole		9	7.6	03		<b>31303</b>
E 18 / 63 A / 3P		3-pole		3	23.0	03		<b>31306</b>

### Comb-type busbar, pitch 27 mm, length 1 m

Type	Centre feed	End feed	Cross-section mm <sup>2</sup>	Pack size	Weight kg/100 u.	PG		Part No.
comb-type busbar, 1-pole, bridge type, pitch 27 mm	130 A	80 A	16	25	19.0	06		<b>31014</b>
	220 A	130 A	35	10	50.0	06		<b>31057</b>
comb-type busbar, 3-pole, bridge type, pitch 27 mm	130 A	80 A	16	10	56.2	06		<b>31012</b>
	220 A	130 A	35	4	125.0	06		<b>31056</b>

### Connection terminal, for comb-type busbars, bridge version

Article	Connection min. – max.	Type	Rated current	Pack size	Weight kg/100 u.	PG		Part No.
connection terminal, side connection	6 - 50 mm <sup>2</sup>	for 31014, 31024, 31309, 31311	125 A	25	2.5	07		<b>31028</b>
connection terminal, side connection		for 31012		25	2.9	07		<b>31029</b>
connection terminal, front connection				25	2.9	07		<b>31085</b>
connection terminal, front connection	25 - 95 mm <sup>2</sup>	for 31057	225 A	3	9.0	07		<b>01198</b>
connection terminal, front connection		for 31056		3	9.3	07		<b>01228</b>

A connection terminal is required for each phase

### End cover

Type	Pack size	Weight kg/100 u.	PG		Part No.
for 2-pole and 3-pole comb-type busbars 16 mm <sup>2</sup>	50	0.1	06		<b>31027</b>
for 3-pole comb-type busbars 35 mm <sup>2</sup>	10	0.2	06		<b>31084</b>