

TRITON®Panel - D0 panel-mounting fuse base

Touch-safe protection in accordance with EN 50274 / DGUV V3 for industrial applications with dual-function terminal on incoming connection, box terminal on outgoing terminal



D0 fuse base, industrial version, pitch 27 mm

Type	Rated voltage	Poles	Connection mm ²	Pack size	Weight kg/100 u.	PG	Part No.
E 14 / 16 A / 1P	400 V	1-pole	1.5 - 35	9	12.8	02	31286
E 14 / 16 A / 3P	400 V	3-pole		3	38.4	02	31288
E 18 / 63 A / 1P	400 V	1-pole		9	13.9	02	31291
E 18 / 63 A / 3P	400 V	3-pole		3	41.4	02	31293

Comb-type busbar, pitch 27 mm, length 1 m

Type	Cross-section mm ²	Centre feed	End feed	Pack size	Weight kg/100 u.	PG	Part No.
comb type busbar, 1-pole, fork type, pitch 27 mm	16	130 A	80 A	25	24.6	06	31024
comb type busbar, 3-pole, fork type, pitch 27 mm	16			10	56.0	06	31026
comb-type busbar, 1-pole, bridge type, pitch 27 mm	16			25	19.0	06	31014
comb-type busbar, 3-pole, bridge type, pitch 27 mm	16			10	56.2	06	31012
	35	220 A	130 A	4	125.0	06	31056

End cover, for insulated comb-type busbars

for 2-pole and 3-pole comb-type busbars 16 mm ²	50	0.1	06	31027
for 3-pole comb-type busbars 35 mm ²	10	0.2	06	31084

Connection terminal, for insulated comb-type busbars, bridge version

Article	Type	Connection mm ²	Rated current	Pack size	Weight kg/100 u.	PG	Part No.
connection terminal, side connection	for 31014, 31024, 31309, 31311	6 - 50	125 A	25	2.5	07	31028
connection terminal, side connection	for 31012	6 - 50	125 A	25	2.9	07	31029
connection terminal, front connection	for 31012	6 - 50	125 A	25	2.9	07	31085
connection terminal, front connection	for 31056	25 - 95	225 A	3	9.3	07	01228

A connection terminal is required for each phase

Label holder

Type	Pack size	Weight kg/100 u.	PG	Part No.
for Triton, snap-on	100	0.1	02	31086

Label, for label holder

Clip 20 x 9	100	0.1	03	31004
-------------	-----	-----	----	--------------