

TRITON®Panel – D fuse base

Touch-safe protection in accordance with EN 50274 / DGUV V3 for industrial applications



D fuse base, industrial version, for screw-in gauge rings

| Type | Rated voltage | Poles | Connection mm ² | Pack size | Weight kg/100 u. | PG | | Part No. |
|--|---------------|-------|----------------------------|-----------|------------------|----|--|--------------|
| E 27 / 25 A / 1P, for screw-in gauge rings | 500 V | 1 | 1.5 - 35 | 9 | 15.2 | 02 | | 31173 |
| E 27 / 25 A / 3P, for screw-in gauge rings | 500 V | 3 | 1.5 - 35 | 3 | 45.7 | 02 | | 31174 |
| E 33 / 63 A / 1P, for screw-in gauge rings | * 500 V | 1 | 1.5 - 35 | 9 | 18.6 | 02 | | 31175 |
| E 33 / 63 A / 3P, for screw-in gauge rings | * 500 V | 3 | 1.5 - 35 | 3 | 53.8 | 02 | | 31176 |

* Conforms to VDE 0636-31, also 690 V AC / 600 V DC

Comb-type busbar, length 1 m

| Type | Cross-section mm ² | Centre feed | End feed | Pack size | Weight kg/100 u. | PG | | Part No. |
|---|-------------------------------|-------------|----------|-----------|------------------|----|--|--------------|
| 1-pole comb-type busbar, insulated, for E27 | 16 | 130 A | 80 A | 25 | 21.5 | 06 | | 31309 |
| 3-pole comb-type busbar, insulated, for E27 | | | | 10 | 51.4 | 06 | | 31310 |
| 1-pole comb type busbar, insulated, for E33 | | | | 25 | 21.0 | 06 | | 31311 |
| 3-pole comb-type busbar, insulated, for E33 | | | | 10 | 50.5 | 06 | | 31312 |

End cover, for insulated comb-type busbars

| Type | Pack size | Weight kg/100 u. | PG | | Part No. |
|--|-----------|------------------|----|--|--------------|
| for 2-pole and 3-pole comb-type busbars 16 mm ² | 50 | 0.1 | 06 | | 31027 |

Connection terminal, for insulated comb-type busbars

| Article | Type | Connection mm ² | Rated current | Pack size | Weight kg/100 u. | PG | | Part No. |
|---------------------------------------|--------------------------------|----------------------------|---------------|-----------|------------------|----|--|--------------|
| connection terminal, side connection | for 31014, 31024, 31309, 31311 | 6 - 50 | 125 A | 25 | 2.5 | 07 | | 31028 |
| connection terminal, side connection | for 31012 | | | 25 | 2.9 | 07 | | 31029 |
| connection terminal, front connection | | | | 25 | 2.9 | 07 | | 31085 |

A connection terminal is required for each phase

Label holder

| Type | Pack size | Weight kg/100 u. | PG | | Part No. |
|---------------------|-----------|------------------|----|--|--------------|
| for Triton, snap-on | 100 | 0.1 | 02 | | 31086 |

Label, for label holder

| | | | | | |
|-------------|-----|-----|----|--|--------------|
| Clip 20 x 9 | 100 | 0.1 | 03 | | 31004 |
|-------------|-----|-----|----|--|--------------|