

High Voltage Differential Probe DP Series Introduction



Applications

- Floating measurements
- Switching power supply design
- Motor drive design
- Electronic ballast design
- CRT display design
- Power converter design and service
- Power device evaluation

Model	DP10013	DP20003
Bandwidth	100MHz	100MHz
Rise Time	3.5ns	3.5ns
Attenuation	50X 500X	200X 2000X
Gain accuracy	±2%	±2%
Maximum Differential Test Voltage (DC+AC PK-PK)	130V (50X) 1300V (500X)	560V (200X) 5600V (2000X)
Maximum input common mode voltage	CAT II 1000V	CAT III 1000V
Input referred noise	≤40mVrms (50X) ≤230 mVrms (500X)	≤160mVrms (200X) ≤920 mVrms (2000X)
Common Mode Rejection Ratio	>80dB (DC) >60dB (100KHz) >50dB (1MHz)	>80dB (DC) >60dB (100KHz) >50dB (1MHz)
Input Impedance	10MΩ/1pF (differential) 5MΩ/2pF (single-ended to ground)	50MΩ/1.25pF (differential) 25MΩ/2.5pF (single-ended to ground)
Output Voltage	≤3V	≤3V
Overrange Alarm	Button light flashes	Button light flashes
Power Supply	DC 5V, USB Supply	DC 5V, USB Supply
Power	0.85W	0.85W
Dimension	14.5cm*6cm*2.7cm	14.5cm*6cm*2.7cm
Input cable length	Approx 60cm	Approx 60cm
Output cable length	Approx 90cm	Approx 90cm
Operating Temperature	0°C~40°C	0°C~40°C
Operating Humidity	10%~85% RH	10%~85% RH

Key performance specifications

- Bandwidths up to 100 MHz
- Maximum Differential Test Voltage (DC+ Peak AC) up to 1300V (DP10013), 5600V (DP20003)
- Switchable attenuation: DP10013(50X, 500X), DP20003(200X, 2000X)