



31 209

Pro pojistkovou techniku s válcovými pojistkami gR

Pojistkové vložky gR

odpovídá IEC / EN 60269-2-1



Velikost	Jm. proud A	Jm. napětí V AC	Jm. vypínací schopnost kA	Ztrátový výkon W	Balení	Hmotnost kg/%	Obrázek	Obj. č.
10 x 38 (gR)	1	660	200	0,9	10	0,6		31 205
	2	660	200	1,0	10	0,6		31 206
	4	660	200	1,1	10	0,6		31 207
	6	660	200	1,6	10	0,6		31 208
	10	660	200	2,1	10	0,6	x	31 209
	12	660	200	3,1	10	0,6		31 210
	16	660	200	4,4	10	0,6		31 211
	20	660	200	5,8	10	0,6		31 212
	25	660	200	6,8	10	0,6		31 213
14 x 51 (gR)	10	690	200	2,6	10	1,9		31 215
	16	690	200	4,7	10	1,9		31 216
	20	690	200	6,0	10	1,9		31 217
	25	690	200	7,6	10	1,9		31 218
	32	690	200	9,5	10	1,9		31 219
	40	690	200	10,0	10	1,9		31 220
	50	690	200	12,0	10	1,9		31 221
22 x 58 (gR)	20	690	200	6,0	10	5,0		31 222
	25	690	200	7,2	10	5,0		31 223
	32	690	200	9,6	10	5,0		31 224
	40	690	200	12,0	10	5,0		31 225
	50	690	200	15,0	10	5,0		31 226
	63	690	200	16,0	10	5,0		31 227
	80	690	200	18,0	10	5,0		31 228
100	690	200	19,0	10	5,0		31 229	

Pojistkové vložky gR

pro použití ve fotovoltaických systémech

10 x 38 (gR)	10	900 V AC / DC	30 kA / 1000 V DC	1,5	10	0,6		31 544
	12	900 V AC / DC	30 kA / 1000 V DC	1,6	10	0,6		31 545
	16	900 V AC / DC	30 kA / 1000 V DC	2,1	10	0,6		31 546
	20	900 V AC / DC	30 kA / 1000 V DC	2,5	10	0,6		31 547